HP Matte Litho-realistic Paper, 3-in Core





The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Deliver high-quality, litho-realistic output

Cost effective alternative to offset paper

Produce high-quality poster art and reproductions. HP Matte Litho-realistic Paper, with a color-stable coating, has the look and feel of heavy, offset paper.

Produce high-quality poster art and reproductions

Deliver prints that withstand the test of time. Providing durable performance indoors, away from direct sun, up to 200 years, in-window up to 1 year unlaminated, up to 2 years laminated on this color-stable, lignin-free paper.

Maintain a smooth workflow, high productivity

To provide trouble-free printing, HP printing materials are designed together with HP DesignJet printers and HP inks. HP Matte Litho-realistic Paper provides excellent image quality in productive modes, instant handling, and flexible processing.

Applications	Benefits The look and feel of a heavy, offset matte paper	
Art reproductions		
Photo enlargements	Excellent water resistance with Original HP pigment-based inks ³	
	Color-stable, lignon-free, buffered paper	
	No optical brighteners	
	Instant handling, flexible processing	
	Excellent film-laminate compatibility	
	Cost-effective alternative to high-end,	
	smooth fine art papers	
	FSC®-certified paper⁴	
	Art reproductions	

Technical specifications



HP Matte Litho-realistic Paper, 3-in Core

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets.

	For the latest ICC profiles/paper presets, please visit HPLF Media.com/np/paperpresets.				
Ink compatability	Original HP pigment- and dye-based inks for HP DesignJet printers and original HP Latex Inks for HP Latex				
Weight	269 g/m² per ISO 536 Test Method				
Thickness	307 microns/12.1 mil per ISO 534 Test Method				
Opacity	> 98% per TAPPI T-425 Test Method				
Brightness	95 per TAPPI T-452 Test Method				
Whiteness	95 per ISO 11475 Test Method				
Finish	Matte				
Operating temperature	15 to 30° C / 59 to 86° F				
Operating humidity	40 to 60% RH				
Display permanence (Indoor home or office)	Up to 200 years with Original HP 771 Vivid Photo Inks or HP 70 Photo Inks or HP 83 UV inks ¹				
Display permanence (Commercial in-window, unlaminated)	Up to 1 year with Original HP 91 or HP 70 Photo Inks²				
Display permanence (Commercial in-window, laminated)	Up to 2 years with Original HP 771 Vivid Photo Inks or HP 91 Photo Inks²				
Water resistance	Water resistant with Original HP 772, HP 91, or HP 70 Photo Inks, or HP 771 Vivid Photo Inks ³				
Dry time	Instant (at 23° C, 50% RH)				
Handling	Fine art papers should be handled with care to avoid scratching				
Shelf life	1 year, unopened in original packaging				
Environmental	Commonly recyclable ⁵ and FSC®-certified paper ⁴				
Storage temperature	0 to 40° C / 32 to 104° F				
Storage humidity	5 to 95% RH				
Country of origin	Product of German	Product of Germany			
Ordering information	Product numbers	Roll sizes	UPC codes	Region	
	K6B77A	610 mm x 30,5 m (24 in x 100 ft)	848412015690	Worldwide	
	K6B78A	914 mm x 30,5 m (36 in x 100 ft)	848412027587	Worldwide	
	K6B80A	1117 mm x 30,5 m (44 in x 100 ft)	848412015720	Worldwide	
	K6B82A	1524 mm x 30,5 m (60 in x 100 ft)	848412015744	United States, Canado Latin America, Europe Middle East, and Africa	
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/MediaWarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .				

- Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see HPLFMedia.com/t/printpermanence.
- 2 Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 Lux/12 hr day. For more information, see HPL EMedia.com/t/printpermanence.
- Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPL FMedia.com/t/printpermanence.
- ⁴ HP has a policy for offering Forest Stewardship Council® (FSC®)-certified papers that are sourced from FSC®-certified forests and other controlled sources. BMG trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please visit HPLFMedia.com.
- ⁵ Can be recycled through commonly available recycling programs.





For detailed information on the HP large format printing materials portfolio and to order, see <u>HPLFMedia.com</u>

© 2023 HP Development Company, L.P. © 2023 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, LP. and is used by Brand Management Group under license from HP Development Company, LP.

