




HP Production Adhesive Vinyl, 3-in Core for HP PageWide Technology



The HP large format printing system—the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Quality prints for day-to-day production

Offer a range of indoor and outdoor displays

Produce vibrant color for your day-to-day production needs. Eye-catching displays—with a permanent, pressure-sensitive adhesive—are ideal for indoor and outdoor applications.

See application and finishing versatility

Designed for a variety of applications and finishing techniques, HP Production Adhesive Vinyl, 3-in Core is a highly versatile media compatible with a variety of laminates to meet a wide range of application needs.

REACH Compliant¹

Meet the environmental goals of your company and your customers with a vinyl that is REACH compliant¹—a regulation of the European Union adopted to improve the protection of human health and the environment from risks that can be posed by chemicals.

Target customers	Applications	Benefits
Advertising agencies	Indoor and outdoor signage	Outstanding image quality for day-to-day production
Graphic artists	POP and retail displays	Fast dry time for easy handling
Sign shops	Trade show and event displays	Designed for a range of applications and finishing methods
Print service providers		Compatible with HP PageWide XL and HP DesignJet printers ²

Technical specifications



HP Production Adhesive Vinyl, 3-in Core for HP PageWide Technology

For the latest ICC profiles/paper presets, please visit [HPLFMedia.com/paperpresets](https://hplfmedia.com/paperpresets).

Ink compatibility	Original PageWide XL pigment inks and Original HP pigment- and dye-based inks for HP DesignJet printers ²			
Weight (without liner)	160 g/m ² per ISO 536 Test Method			
Weight (with liner)	300 g/m ² per ISO 536 Test Method			
Thickness (without liner)	144 microns/5.7 mil per ISO 534 Test Method			
Thickness (with liner)	271 microns/10.7 mil per ISO 534 Test Method			
Adhesive	Solvent, acrylic permanent adhesive			
Adhesion, initial	> 5 N/in after 20 minutes over stainless steel			
Adhesion, 24-hour dwell	> 10 N/in after 24 hours over stainless steel			
Dimensional stability (%)	<5% over aluminum			
Elongation at break	>100% MD; >100% CD			
Opacity	>99% per TAPPI T-425 Test Method and ISO 2471 Test Method			
Brightness	100 per ISO 2470 Test Method			
Whiteness	127 per ISO 11475 Test Method			
Finish	Matte			
Operating temperature	15 to 30° C / 59 to 86° F			
Operating humidity	20 to 65% RH			
Dry time	Instant dry			
Lamination	Cold lamination, can be laminated with most commercially available cold laminate films			
Shelf life	1 year, unopened in original packaging			
Storage temperature	15 to 30° C / 59 to 86° F			
Storage humidity	20 to 65% RH			
Printer setting	Recommend using HP Matte Polypropylene as the media setting for HP PageWide XL printers			
Country of origin	Product of China			
Environmental	REACH compliant ¹			
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/hp/mediawarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus .			
Ordering information	Product numbers	Roll sizes	UPC codes	Region
	1AF11A	36 in x 150 ft (914 mm x 45.7 m)	848412020748	United States, Canada, Latin America, Europe, Middle East, and Africa
	2HY31A	40 in x 150 ft (1016 mm x 45.7 m)	848412021905	United States, Canada, Latin America, Europe, Middle East, and Africa

¹ See the HP REACH Declaration published at [HP Printing Products and Consumable Supplies](https://hplfmedia.com/hp/printingproductsandconsumablesupplies).

² Compatibility with HP DesignJet printers requires 3-in core adapter.

